


Microphone Cable SC-Square 4-Core MKII; 4 x 0,20 mm²; PVC Ø 6,50 mm; black

Art. No.: 200-0301NE

ANALOG

OFC



General Data

Article number :	200-0301NE
Name :	SC-Square 4-Core MKII
EAN :	4049371193368
Properties :	Analog
Properties :	OFC oxygen free copper
Application area :	Stage / live
Application area :	Mobile outdoor / indoor
Application area :	Installation
Application :	Microphone Cable
Colour :	black
BPVo-Euroclass :	Fca

Technical Data

Signal transmission :	symmetrical
Construction :	(4LI2Y0,20mm ²)(ST)DY
Jacket material :	PVC
Jacket Ø [mm] :	6,50
Number of Channels (audio) :	1
Inner conductor (audio) :	4
Inner conductor (audio) [mm ²] :	0,20
Inner conductor Ø (audio) [mm] :	0,50
AWG (audio) :	25
Shielding :	Copper spiral shielding tinned + conductive fleece-foil
Shielding factor [%] :	100
Copper strands (audio) :	102
Copper strand Ø (audio) [mm] :	0,05
Conductor insulation material :	PE
Weight per 1 m [g] :	53
UV-resistant :	yes
Fire load per m [kWh] :	0,22
Style variant :	round
Packing :	100 m spool
Packing :	500 m spool
Temperature min. [°C] :	-25
Temperature max. [°C] :	70
Width [mm] :	6,5
Height [mm] :	6,5

Electrical Data

Capac. cond./cond. per 1 m (audio) [pF] :	65
Capac. cond./shield. per 1 m (audio) [pF] :	120
Impedance [Ω] :	95

Insulation resist. per 1 km [GΩ] :	0,2
Insulation resist. per 1 km (audio) [GΩ] :	0,2
Conductor resistance per 1 km [Ω] :	98
Shield. resistance per 1 km [Ω] :	20