

Speaker Cable SC-AQUA MARINEX SPEAKER 240; 2 x 4,00 mm²; PUR-SR Ø 11,20 mm; black

Art. No.: 440-0241AQ

AQUA **HALOGEN-FREE** **OFC** **PUR**



General Data

Article number :	440-0241AQ
Name :	SC-AQUA MARINEX SPEAKER 240
EAN :	4049371194457
Properties :	Analog
Properties :	Halogen-free / LSZH
Properties :	PUR
Properties :	Digital 75 Ω
Properties :	Underwater / submerged
Application area :	Stage / live
Application area :	Mobile outdoor / indoor
Application area :	Installation
Application area :	ELA 100 V
Application :	Speaker Cable
Colour :	black
BPVo-Euroclass :	Fca

Technical Data

Jacket material :	PUR-SR
Jacket Ø [mm] :	11,20
Number of Channels (audio) :	1
Inner conductor (audio) :	2
Inner conductor (audio) [mm ²] :	4,00
AWG (audio) :	11
Shielding :	CU braiding + special protective banding
Shielding factor [%] :	85
Copper strands (audio) :	224
Copper strand Ø (audio) [mm] :	0,15
Conductor insulation material :	PO
Conductor insulation Ø [mm] :	3,80
Weight per 1 m [g] :	178
UV-resistant :	yes
Fire load per m [kWh] :	0,55
Style variant :	round
Packing :	bulk stock
Temperature min. [°C] :	-40
Temperature max. [°C] :	80
Width [mm] :	11,2
[mm] :	11

Electrical Data

Capac. cond./cond. per 1 m (audio) [pF] :	80
Insulation resist. per 1 km [GΩ] :	1

Insulation resist. per 1 km (audio) [GΩ] :	1
Conductor resistance per 1 km [Ω] :	5,09
Shield. resistance per 1 km [Ω] :	8,1